/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.


/ Features

High f_T.


/ Applications

High frequency general-purpose amplifier applications.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Emitter PIN 3 Collector


/ h_{FE} Classifications & Marking


h_{FE} Classifications Symbol	2	3	4
h_{FE} Range	40 80	60 120	90 180
Marking	HJ2	J3H	HJ4


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	25	V
Collector to Emitter Voltage	V_{CEO}	20	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current	I_C	30	mA
Collector Power Dissipation	P_C	150	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}		


/ Electrical Characteristic Curve













/ Package Dimensions



/ Marking Instructions



H


J

2 h_{FE}

Note:

H	Company Code
J	Product Type Code
2	h_{FE} Classifications Symbol Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1	25	150		60	90sec;	1.Preheating:25~150 , Time:60~90sec.
2	245±5				5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3			2	10	/sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Units Dimension (unit mm^3)