˜Yت

SOT-323 NPN Silicon NPN transistor in a SOT-323 Plastic Package.

◕ È

High f_T, small $C_{C.rbb'}$ and high gain, small NF.

٧ ي

High-Frequency amplifier transistor

Ɲ ف̊ ᾷ ≠ ع



ã ⅄ ʊ̃



PIN1 Emitter PIN 2 Base PIN 3 Collector

ŁL ʜ ɔ̇

h_{FE} Classifications Symbol	N	P
h_{FE} Range	56 120	82 180
Marking	1DHN	1DHP

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	11	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current - Continuous	I_C	50	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

ᵘ ĖÒĻ ʃ



ł. Ļ Ω



1D

H

N h_{FE}

Note:

1D: Product Type.

H: Company Code.

N: h_{FE} Classifications Symbol

ŧħ ʃ ╗ ẘ ´E ⅵ ʃ ᾠ ᴗ Wh p shudwxuh Suriloh iru LU Uhior z Vroghulqj+Se0luhh,



Note:

1 25 150 60 90sec;

2 245±5 5±0.5sec;

3 2 10 /sec.

1.Preheating:25~150 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

⅃ ὖ ɋ ⁻ ˋY Ţ

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

ɒ ⊢ ⊂—

/ REEL

Package Type	Units					Dimension (unit mm^3)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

ä ⅴ ⌊ ̋Ω