/ Descriptions

TO-252
Voltage Regulator in a TO-252 Plastic Package.

/ Features

1.5A,

3-Terminal regulators ,output current up to 1.5A, internal thermal overload protection and short-circuit limiting, HF Product.

/ Applications

Voltage Regulator.

/ / Equivalent Circuit or Application Circuit



/ Pinning



PIN1 IN PIN 2 4 GND PIN 3 OUT

/ Marking

See Marking Instructions.

/ Package Dimensions



/ Marking Instructions



BR

79D12

****

Note:

BR:	Company Code
79D12:	Product Type
****:	Lot No. Code, code change with Lot No

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



1	150 180	60 90sec;	Note: 1.Preheating:150~180 , Time:60~90sec.
2	245±5	5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3	2 10 /sec.		3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm³)		
TO-252	2,500	2	5,000	6	30,000	13 ×16	360×360×50	380×335×366

/ TUBE

Package Type	Units					Dimension (unit mm³)		
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

/ Notices