"Yـ / Descriptions

Silicon NPN transistor in a SOT-323 Plastic Package.


◕ È / Features

High current, low voltage complementary pair with BC807W.

¥ ٍ / Applications

General purpose switching and amplification.

Л ً ٖ ≠ ع / Equivalent Circuit



ẵ ﻸ ٗ / Pinning



PIN1 Emitter PIN 2 Base PIN 3 Collector


ł. ʜ ڬ / Marking


h_{FE} Classifications Symbol	16	25	40
h_{FE} Range	100 250	160 400	250 600
Marking	H6A	H6B	H6C


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	50	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	500	mA
Peak Collector Current - Continuous	I_{CM}	1.0	A
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	I_{CBO}	V_{CB}=20V I_E=0			5.0	μA
Emitter Base Cut-Off Current	I_{EBO}	V_{EB}=5.0V I_C=0			0.1	μA
DC Current Gain	h_{FE}	V_{CE}=1.0V I_C=100mA	100		600	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=500mA I_B=50mA			0.7	V
Base to Emitter Voltage	V_{BE}	V_{CE}=1.0V I_C=500mA			1.2	V

≠ ∃ ÃΆ´E ∀ ƒ / Electrical Characteristic Curve











ᵘ Ė Ồ Ļ ƒ / Package Dimensions

SOT-323 单位：mm



Ł. Ł Ω / Marking Instructions



H


6A

Note:

H: Company Code.

6A: Product Type.

₧ʃ ╕ẘ´E ᛘ ƒ(ὼ ᴈs) / Wh p shudwxuh Sur loh i ru LU Uhio r z Vroghulq j+Se0 luhh,



Note:

1 25 150 60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2 245 5 5 0.5sec;	2.Peak Temp.:245 5 , Duration:5 0.5sec.
3 2 10 /sec.	3. Cooling Speed: 2~10 /sec.

ᛘ ὐ ɋ ̄ ̀Y Ţ / Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260±5 Time:10±1 sec

ɒ Ŀ ≮— / Packaging SPEC.

/ REEL

Package Type	Units					Dimension		(unit mm^3)

ä ᴠ Ļ Ὼ / Notices