TO-251 ĶĶĿ N ŏ MOS ĵ ŵ Ẕ ˥ N-CHANNEL MOSFET in a TO-251 Plastic Package.

Ħ ɔ U/Ħ ɾ ɨ ɔ ķ/Ầ ʜ ȣ ỷ ȍ
Low gate charge, low crss, fast switching.


ȩ̂ ɤ ı ' GF2GF ȩ̈Ω ⁼ ı ' Ầ ʜ
These devices are well suited for high efficiency switching DC/DC converters and switch mode power supplies.

v ̈Ω Parameter	ϒ N Symbol	̈Ω Ö Rating	D Ꮋ Unit
Drain-Source Voltage	V_{DSS}	800	V


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions




ب ˝ χ	
BR χ	ѭ ϛ и Ґђ
6Q ; 3 χ	ѭ ʒ ɴ Ґђ
---- χ	ѭ ɨ ғ ӈ̈ ɴ Ґђ ɪ ɕ ɨ ғ ӈ̈ ɴ Ψ ϼ

Note:

BR:	Company Code
3N80:	Product Type.
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı `H ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ł ı `H ڑ `Y ㅅ ㎛ 5 ° 0.5sec;

3 ì ˙ ٦ ˛ ɔ ෯ ỷ ㎛ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:255 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ł `H ڑ χ 10 ° 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

¨Ω ţ ץ Ł / BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	只 袋	袋 箱	只 箱	盒 箱	只	袋	箱	

˛ ٦ ץ Ł / TUBE