## / Descriptions

PDFN5Ö6 ṂṂ Ł VIF ₌ ᵍ‾ ‖ ㄱ

SiC Schottky Barrier Diode in a PDFN5×6 Plastic Package.

## / Features


ˈΩ ǎ Ḥ ı ѽ ' ㅈ ı ṇ ꜰ β


Low power loss, high efficiency, HF Product.

## [redacted]

ἧ ㅈ ḷ ㅈ ㅑ ᶻ ↄ ㅣ ̃Ω ㅣ ‖ ㄱ ı ㅅ ㅣ ‖ ㄱ

For high frequency, high voltage, high current rectifier diode, freewheeling diode




PIN 1,2,3 χ Anode PIN5-8 χ Cathode PIN 4 χ NC

## / Marking


ð м ㄱ ب ˝


See Marking Instructions.

| v ̈Ω<br>Parameter | ϒ N<br>Symbol | ̈Ω Ö<br>Rating | D Ч<br>Unit |
|---|---|---|---|
| Peak Repetitive Reverse Voltage | $V_{RRM}$ | 650 | V |
| Maximum RMS Voltage | $V_{RMS}$ | 455 | V |
| Maximum DC blocking Voltage | $V_{DC}$ | 650 | V |
| Continuous Forward Current,$T_C$=150 | $I_F$ | 6 | A |
| Peak forward surge current,tp=8.3ms | $I_{FSM}$ | 52 | A |
| Total power disspation | $P_D$ | 53 | W |
| Typical Thermal Resistance Junction to Case | R θ JC | 2.8 | /W |
| Operation Junction Temperature and Storage Temperature | $T_J$, $T_{STG}$ | -55~+175 | |

| v ̈Ω<br>Parameter | ϒ N<br>Symbol | ╝ ː ˥ Ţ<br>Test Conditions | ώ ṇ Ö<br>Min | Ɛ ʒ Ö<br>Typ | ώ ᶻ Ö<br>Max | D Ч<br>Unit |
|---|---|---|---|---|---|---|
| Reverse Voltage | $V_R$ | | 650 | - | - | V |
| Forward Voltage | $V_F$ | $I_F$=6A $T_C$=25 | - | 1.27 | 1.5 | |
| | | $I_F$=6A $T_C$=175 | - | 1.38 | 1.6 | |
| Instantaneous Reverse Current | $I_R$<br>Note 1 | $V_R$=650V $T_a$=25 | - | 4 | 50 | μA |
| | | $V_R$=650V $T_a$=175 | - | 200 | 200 | |
| Total capacitive charge | $Q_C$ | VR =650V,IF =6A<br>di/dt = 200A/μs | - | 17 | - | nC |


## / Electrical Characteristic Curve



## / Package Dimensions


PDFN5×6 Unit:mm




| Symbol | Millimeters MIN | TYP. | MAX |
|---|---|---|---|
| A | 5.90 | 6.00 | 6.10 |
| B | 4.90 | 5.00 | 5.10 |
| b | 3.375 | 3.475 | 3.575 |
| B1 | 4.80 | 4.90 | 5.00 |
| l | 0.06 | 0.13 | 0.20 |
| L1 | 1.10 | – | – |
| L7 | 0.51 | 0.61 | 0.71 |
| P | 1.15 | 1.30 | 1.45 |
| θ | 8° | 10° | 12° |
| Φ | 1.10 | 1.20 | 1.30 |

Rev.01 202209

## / Marking Instructions





| | |
|---|---|
| ͡ ˝ χ | |
| EU χ | ꞵꞃ ꝛ ᴎ ᑎ ᒃ |
| SC06650 χ | ꞵꞃ ʒ ᴺ ᑎ ᒃ |
| ---- χ | ꞵꞃ ꞌ ꜰ ᵑ̈ ᴺ ᑎ ᒃ ı ₡ ꞌ ꜰ ᵑ̈ ᴺ Ψ ᖘ |

Note χ

| | |
|---|---|
| BR χ | Company Code |
| SC06650 χ | Product Type Code |
| ****: | Lot No. Code, code change with Lot No |

## ( ) /




ڍ ˝ χ

1 Ĺ♬□ẙ 150Ḱ180ɬ ı `H ڑ 60Ḱ90sec;

2 Š Ë □ẙ 245°5ɬ ı `H ڑ 'Y ʌ ʁ 5°0.5sec;

3 ì ˙ ϒ ˛ ɔ ѕ ẙ ʁ 2Ḱ10ɬ /sec.

Note:

1.Preheating:150~180ɬ, Time:60~90sec.

2.Peak Temp.:245°5ɬ, Duration:5°0.5sec.

3. Cooling Speed: 2~10ɬ /sec.

## / Resistance to Soldering Heat Test Conditions

□ẙ χ 260°5ɬ `H ڑ χ 10°1 sec. Temp.:260±5 Time:10±1 sec

## / Packaging SPEC.

ɔ` ɣ Ł / REEL

| Package Type Ṃ Ł ė Ǻ | Units | | | | | Dimension | | (unit mm³) |
|---|---|---|---|---|---|---|---|---|
| | Units/Reel ᴱ 2ɔ` | Reels/Inner Box ɔ` 2 ¨ | Units/Inner Box ᴱ 2 ¨ | Inner Boxes/Outer Box ¨ 2ϒ | Units/Outer Box ᴱ 2ϒ | Reel | Inner Box ¨ | Outer Box ϒ |
| PDFN5×6 | 5,000 | 2 | 10,000 | 6 | 60,000 | 13"×12 | 360×360×50 | 380×335×366 |

## / Notices