/ Descriptions

SOT-23 NPN

Silicon NPN Digital transistor in a SOT-23 Plastic Package.


/ Features

With built-in bias resistors, simplify circuit design, reduce a quantity of parts and manufacturing process,HF Product.


/ Applications

Switching, inverter circuit, interface circuit and driver circuit applications.

/ Equivalent Circuit



/ Pinning




PIN 1 IN PIN 2 GND PIN 3 OUT


/ h_{FE} Classifications & Marking

Marking	H64


/ Electrical Characteristic Curve







/ Package Dimensions



DTC114YKA

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



			Note:
1	150 180	60 90sec;	1.Preheating:150~180 , Time:60~90sec.
2	245±5	5±0.5sec;	2.Peak Temp.:245±5 , Duration:5±0.5sec.
3		2 10 /sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 7>û ˜ E	Units ;>û ¦H					Dimension ;>û p . (unit ÆEmm³)	
	Units/Reel / --	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box×