/ Descriptions

Silicon NPN transistor in a SOT-23 Plastic Package.

/ Features

High G_{pe}.

/ Applications

HF,VHF band amplifier application.

/ Equivalent Circuit



/ Pinning



PIN 1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	R	O	Y
h_{FE} Range	40 80	70 140	120 240
Marking	HRR	HRO	HRY

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	35	V
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Base Voltage	V_{EBO}	4.0	V
Collector Current	I_C	50	mA
peratCurgrge			50

/ Electrical Characteristic Curve





/ Package Dimensions

SOT-23

单位：mm



/ Marking Instructions



Note:

	Company Code
R	Product Type
	h_{FE} Classifications Symbol

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



	Note:
1 25 150 60 90sec;	1.Preheating:25~150 , Time:60~90sec.
2 245 5 5 0.5sec;	2.Peak Temp.:245 5 , Duration:5 0.5sec.
3 2 10 /sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec.	Temp.:260 5 Time:10 1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension		(unit mm^3)