/ Descriptions

VRW0656 ṂṂ Ł QSQ ÆṀ ч s ǁ ㄱ Silicon NPN transistor in a SOT-323 Plastic Package.

/ Features

лъ NWD5348 Йį ´


Complementary to KTA2015

/ Applications

₹ˆ˙ ˝ ψ ѽ ᶻ ⊐ ₹˝Ω

General purpose application, switching application.

/ Equivalent Circuit



/ Pinning



PIN1 χ Emitter PIN 2 χ Base PIN 3 χ Collector


/ Marking

h_{FE} Classifications Symbol	O	Y
h_{FE} Range	70 140	120 240
Marking	HWO	HWY


KTC4076

Rev.E Mar.-2016


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



ᴗ ˝ χ

K χ ᵻᵻ ϛ ᵘ Ꮷ

Z χ ᵻᵻ ȝ ᴺ Ꮷ

R χ ᵻᵻ k ᵻᴴ ‘ ⁶ Ꮷ


Note:

H: Company Code.

W: Product Type.

O: h_{FE} Classifications Symbol

( ) /



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı ˋH ڑ 60 Ḱ 90sec;

2 Š Ë □ ỷ 245 ° 5 ł ı ˋH ڑ ˋY ﾊ ㎛ 5 ° 0.5sec;

3 ì ˙ ﾘ ˛ ɔ ﻉ ỷ ㎛ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:245 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 260 ° 5 ł ˋH ڑ χ 10 ° 1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

ɔ ` ﾔ Ł / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices