/ Descriptions

WR0553I ṂṂ Ł ⸗ ᵍ⁀ ‖ ㄱ

Schottky Diode in a TO-220F Plastic Package.

/ Features

Ḧ* ᵇ я ∪ ı Ḧ ı ă ̈Ω ı ≍ ̃ω ' ظΦ


Low forward voltage drop,low power losses,High efficiency operation.

/ Applications


ἓ ≍ ļ ڜ Ψ ʜ ı Ã ʜ ɔ ◊ ı ㅅ ㅣ‾ ‖ ㄱ ı RU0lqj⁀ ‖ ㄱ ı GF0GF ج ̈Ω ʜ ⊐ ɔ – ɾ ᵇ Ȝ ï

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode


/ h_{FE} Classifications & Marking

ծ м ㄱ ب ˝ See Marking Instructions.


v ̈Ω
Parameter

/ Electrical Characteristic Curve


IFSM




IR - VR




CJ - VR



/ Package Dimensions



/ Marking Instructions




◌̇ ˝ χ	
EU χ	ꟻ ϛ ᴎ Γϧ
0Y43483 χ	ꟻ ȝ ᴺ Γϧ
ı=	ꟻ Ṃ Ꝉ Γϧ
FW=	ꟻ ɲ ɯh ⅃ ⚌
---- χ	ꟻ ı ꜰ ñ ᴺ Γϧ ı ϕ ı ꜰ ñ ᴺ Ψ ק

Note:

BR:	Company Code
LV10150:	Product Type.
F:	Package Code
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı `H ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ł ı `H ڑ `Y ㄏ ㎛ 5 ° 0.5sec;

3 ì ˙ ㄚ ˛ ɔ ѡ ỷ ㎛ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:255 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ł `H ڑ χ 10 ° 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

¨Ω ţ ㄚ Ł / BULK

Package Type	Units					Dimension		(unit mm³)

˛ ㄱ ㄚ Ł / TUBE

Package Type	Units					Dimension		(unit mm³)

/ Notices