


v ̈Ω Parameter	ϒ N Symbol	̈Ω Ö Rating	D Ђ Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RM} V_{RSM} V_{DC}	150	V
RMS Reverse Voltage	V_{RMS}	105	V


Average Rectified Forward Current Ic0 Tw(RMS)Tj10.5 0tive Reverse e Reo36.1481[150)-4.3

/ Electrical Characteristic Curve











/ Package Dimensions




/ Marking Instructions



◌ ˝ χ	
EU χ	⊮ ϛ ᴎ Γ ᵬ
0Y63483 χ	⊮ ғ ᵝ ȝ ᴺ
FW=	⊮ ᴖ ᵮ ᒧ ⎯
---- χ	⊮ ᵻ ғ ᵰ ᴺ Γ ᵬ ı ₡ ᵻ ғ ᵰ ᴺ Ψ ᖘ
Note:	
BR:	Company Code
LV30150 χ	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ł ı `H ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ł ı `H ڑ `Y ㅅ ㎛ 5 ° 0.5sec;

3 ì ˙ ㅓ ˛ ↄ ෯ ỷ ㎛ 2 Ḱ 10 ł /sec.

Note:

1.Preheating:25~150 ł , Time:60~90sec.

2.Peak Temp.:255 ° 5 ł , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ł /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ł `H ڑ χ 10 ° 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

¨Ω ţ ㅓ Ł / BULK

Package Type	Units					Dimension		(unit mm³)
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

˛ ㅓ ㅓ Ł / TUBE

Package Type	Units					Dimension		(unit mm³)
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices